

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

SECTION 1. IDENTIFICATION

Product name : Solstice® 513A

Number : 000000022892

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 800-522-8001
+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : clear colourless

Odor : slight ether-like

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

00000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Storage:**
Protect from sunlight. Store in a well-ventilated place.Hazards not otherwise
classified: May cause cardiac arrhythmia.
May cause frostbite.
May cause eye and skin irritation.**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Mixture

Chemical name	CAS-No.	Concentration
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	56.00 %
1,1,1,2-Tetrafluoroethane	811-97-2	44.00 %

SECTION 4. FIRST AID MEASURES

Inhalation

: Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.

Skin contact

: After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with

00000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

Indication of immediate medical attention and special treatment needed, if necessary : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : The product is not flammable.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards during firefighting : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
In case of fire hazardous decomposition products may be produced such as:
Hydrogen halides
Hydrogen fluoride
Carbon monoxide
Carbon dioxide (CO₂)
Carbonyl halides

00000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit. No unprotected exposed skin areas.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Wear personal protective equipment. Unprotected persons must be kept away. Remove all sources of ignition. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area. After release, disperses into the air. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Avoid accumulation of vapours in low areas. Unprotected personnel should not return until air has been tested and determined safe. Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so. The product evaporates readily.

Methods and materials for containment and cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Handle with care. Avoid inhalation of vapour or mist. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Use only in well-ventilated areas. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Follow all standard safety precautions for handling and use of compressed gas cylinders. Use authorized cylinders only.

00000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Protect cylinders from physical damage.
 Do not puncture or drop cylinders, expose them to open flame or excessive heat.
 Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
 Do not remove screw cap until immediately ready for use.
 Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.
 Can form a combustible mixture with air at pressures above atmospheric pressure.

Storage

Conditions for safe storage, including any incompatibilities : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
 Keep containers tightly closed in a dry, cool and well-ventilated place.
 Storage rooms must be properly ventilated.
 Ensure adequate ventilation, especially in confined areas.
 Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.
 Avoid contact with skin, eyes and clothing.
 Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.
 Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection : Wear as appropriate:
 Safety glasses with side-shields
 If splashes are likely to occur, wear:
 Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves
 In case of contact through splashing:
 Protective gloves
 Neoprene gloves
 Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	TWA : Time weighted average	(500 ppm)	2009	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	TWA : Time weighted average	(500 ppm)	03 15 2010	Honeywell:Limit established by Honeywell International Inc.
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	STEL : Short term exposure limit	(1,500 ppm)	03 15 2010	Honeywell:Limit established by Honeywell International Inc.
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

1,1,1,2-Tetrafluoroethane	811-97-2	TWA : Time weighted average	4,240 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
---------------------------	----------	--------------------------------------	----------------------------	------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquefied gas
Color	: clear colourless
Odor	: slight ether-like
Odor threshold	: Note: no data available
pH	: Note: Not applicable
Melting point/range	: Note: no data available
Boiling point/boiling range	: -29.2 °C
Flash point	: Note: Not applicable
Flammability	: The product is not flammable.
Lower explosion limit	: Note: None
Upper explosion limit	: Note: None
Vapor pressure	: 0.637 MPa at 21.1 °C(70.0 °F)
Vapor density	: 3.83 Note: (Air = 1.0)
Density	: 1.15 g/cm3 at 21.1 °C

00000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Water solubility	: Note: no data available
Partition coefficient: n-octanol/water	: Note: no data available
Ignition temperature	: Note: no data available
Auto-ignition temperature	: > 750 °C
Decomposition temperature	: > 250 °C Note: To avoid thermal decomposition, do not overheat.
Viscosity, dynamic	: Note: no data available
Viscosity, kinematic	: Note: no data available

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
Incompatible materials	: Potassium Calcium Powdered metals Finely divided aluminium Finely divided magnesium Zinc
Hazardous decomposition products	: Halogenated compounds Hydrogen fluoride Carbonyl halides Carbon oxides

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

SECTION 11. TOXICOLOGICAL INFORMATION

- Acute inhalation toxicity
2,3,3,3-Tetrafluoroprop-1-ene : LC50: > 400000 ppm
Exposure time: 4 h
Species: Rat
Method: OECD Test Guideline 403
- 1,1,1,2-Tetrafluoroethane : LC50: > 500000 ppm
Exposure time: 4 h
Species: Rat
- Skin irritation : Note: Not applicable study technically not feasible
- Eye irritation : Note: Not applicable study technically not feasible
- Sensitisation
2,3,3,3-Tetrafluoroprop-1-ene : Dermal
Note: Not applicable, as this product is a gas.
study technically not feasible
- 1,1,1,2-Tetrafluoroethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
50 000 ppm
Lowest observed effect level
75 000 ppm
- Repeated dose toxicity
2,3,3,3-Tetrafluoroprop-1-ene : Species: Rat
Application Route: Inhalation
Exposure time: (2 Weeks)
No-observed-effect level: 50000 ppm
Method: OECD Test Guideline 412
- Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOAEL (No observed adverse effect level): 50000 ppm
Method: OECD Test Guideline 412

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Species: Rat
 Application Route: Inhalation
 Exposure time: (13 Weeks)
 NOAEL (No observed adverse effect level): 50000 ppm
 Method: OECD Test Guideline 413

Species: Rabbit, male
 Application Route: Inhalation
 Exposure time: (28 d)
 No-observed-effect level: 500 ppm
 Method: OECD Test Guideline 412
 There are no observed toxicological effects, which result in classification as a specific target organ toxicant.

Species: Rabbit, female
 Application Route: Inhalation
 Exposure time: (28 d)
 No-observed-effect level: 1000 ppm
 Method: OECD Test Guideline 412
 There are no observed toxicological effects, which result in classification as a specific target organ toxicant.

Species: Mini-pig
 Application Route: Inhalation
 Exposure time: (28 d)
 NOAEL (No observed adverse effect level): 10000 ppm
 highest exposure tested

1,1,1,2-Tetrafluoroethane : Species: Rat
 NOEL: 40000 ppm

Genotoxicity in vitro
 2,3,3,3-Tetrafluoroprop-1-ene : Test Method: Ames test
 Result: 20% and higher, positive in TA 100 and e. coli WP2 uvrA, negative in TA98, TA100, and TA1535.
 Method: OECD Test Guideline 471

1,1,1,2-Tetrafluoroethane : Note: In vitro tests did not show mutagenic effects
 : Test Method: Chromosome aberration test in vitro
 Cell type: Human lymphocytes
 Result: negative
 Method: OECD Test Guideline 473
 Note: Dose 760,000 ppm

Genotoxicity in vivo

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

- 2,3,3,3-Tetrafluoroprop-1-ene : Species: Mouse
Cell type: Micronucleus
Dose: up to 200,000 ppm (4 hour)
Method: OECD Test Guideline 474
Result: negative
- : Test Method: Unscheduled DNA synthesis
Dose: up to 50,000 ppm (4 weeks)
Method: OECD Test Guideline 486
Result: negative
- : Species: Rat
Cell type: Micronucleus
Dose: up to 50,000 ppm (4 weeks)
Method: OECD Test Guideline 474
Result: negative
- Carcinogenicity
2,3,3,3-Tetrafluoroprop-1-ene : Species: Rat
Note: Not classified as a human carcinogen. Substance not expected to be a carcinogen based on available data.
- Further information : Note: Rapid evaporation of the liquid may cause frostbite. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

- Toxicity to fish
2,3,3,3-Tetrafluoroprop-1-ene : LC50: > 197 mg/l
Exposure time: 96 h
Species: Cyprinus carpio (Carp)
Method: OECD Test Guideline 203
Note: No demonstrable toxic effect in saturated solution.

- Toxicity to daphnia and other aquatic invertebrates
2,3,3,3-Tetrafluoroprop-1-ene : EC50: > 83 mg/l
Exposure time: 48 h

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

Toxicity to algae
2,3,3,3-Tetrafluoroprop-1-ene : EC50: > 100 mg/l
Species: Scenedesmus capricornutum (fresh water algae)
Method: OECD Test Guideline 201

Toxicity to bacteria : Growth inhibition
EC10: > 730 mg/l
Exposure time: 6 h
Species: Pseudomonas putida
Test substance: 1,1,1,2-tetrafluoroethane (HFC-134a)

Elimination information (persistence and degradability)

Bioaccumulation
2,3,3,3-Tetrafluoroprop-1-ene : Note: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Biodegradability : Result: Not rapidly biodegradable
Value: 3 %
Test substance: 1,1,1,2-tetrafluoroethane (HFC-134a)
Method: OECD 301 D

Further information on ecology**Ecotoxicology Assessment**

Results of PBT assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT)., This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Additional ecological information : Accumulation in aquatic organisms is unlikely.
This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.
This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere.
To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

00000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Note : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT	UN/ID No.	: UN 3163
	Proper shipping name	: LIQUEFIED GAS, N.O.S. (R-1234yf, 1,1,1,2-Tetrafluoroethane)
	Class	: 2.2
	Packing group	
	Hazard Labels	: 2.2
IATA	UN/ID No.	: UN 3163
	Description of the goods	: LIQUEFIED GAS, N.O.S. (R-1234yf, 1,1,1,2-Tetrafluoroethane)
	Class	: 2.2
	Hazard Labels	: 2.2
	Packing instruction (cargo aircraft)	: 200
	Packing instruction (passenger aircraft)	: 200
IMDG	UN/ID No.	: UN 3163
	Description of the goods	: LIQUEFIED GAS, N.O.S. (R-1234yf, 1,1,1,2-TETRAFLUOROETHANE)
	Class	: 2.2
	Hazard Labels	: 2.2
	EmS Number	: F-C, S-V
	Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection : All components of this product are on the Canadian DSL

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

Act (CEPA). Domestic
Substances List (DSL)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : Not in compliance with the inventory

China. Inventory of Existing Chemical Substances : Not in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : Not in compliance with the inventory

TSCA 12B : US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

2,3,3,3-Tetrafluoroprop-1-ene 754-12-1

National regulatory information

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E) :

2,3,3,3-Tetrafluoroprop-1-ene 754-12-1

SARA 302 Components : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard
Acute Health Hazard

000000022892

Version 1.2

Revision Date 05/08/2018

Print Date 05/25/2022

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 03/28/2018

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group